Brass (Cu70Zn30)

Sheets



Material Designation		
ASTM	C26000	
JIS	C2600	
INDIAN	CuZn30	
EN	CW505L	
BS	CZ105	

Chemical Composition (%)		
68.50 - 71.50 <0.05		
Remaining		

Applications		
Watch Dials Jewellery Radiator Cores		
Locks Thermostat Connectors		

Specification

Thickness 0.3 - 4 mm Width 350 - 1000 mm Length 400 - 6000 mm

Temper O, 1/4H, 1/2H, 3/4H, H, EH, SH

Properties

Cold Workability Excellent
Electroplating Capacity Excellent
Forming Properties Good
Mechanical Strength Good

Description

70/30 alloy is as Catridge Brass which contains 70% copper and 30% Zinc. This alloy features very good mechanical properties and corrosion behavior comparable to copper. It is having outstanding deep drawing properties. 70/30 alloy is the most common brass in sheet form. It has the distinctive clear bright yellow colour normally associated with brass. This alloy offers the best combination of strength and ductility of all copper-base alloys.

Value Proposition

- Competitive Pricing
- Flexible LME price fixation
- Product Customization

- Quality Assurance
- Committed to deliveries
- Standard export pallet packing

This data is general technical specification; Binding technical specifications will be as per agreement.

PANBASE RESOURCES PVT LTD +91 22 6712 6823 sales@panbase.net www.panbase.net 1207, 12th Floor, Mayuresh Chambers, Sector 11, CBD Belapur, Navi Mumbai – 400 614, India