## Brass (Cu85Zn15) Strips



Material Designation		Chemical Composition (%)		Applications	
ASTM JIS INDIAN EN BS	C23000 C2300 CuZn15 CW502L CZ102	Cu Fe Pb Zn	84.00 - 86.00 <0.05 <0.02 Remaining	Zipper Puller Condenser Tubes Nuts & Bolts Heat Exchangers Fire Extinguisher	

Specification					Properties		
Thickness Width	0.025 - 5 mm	ID	80 - 500 mm		Solder Ability Conductivity	Excellent Good	
Length	4 - 1220 mm -	OD Coil Wt	- 10 - 2000 Kg		Formability	Excellent	
Temper	O , 1/4H , 1/2H , 3/4H , H , EH , SH				Corrosion Resistance	Good	

## Description

85/15 alloy is also known as Red Brass which contains 85% copper and 15% Zinc. It is an alloy used in numerous decorative applications. Also useful as a lower strength electrical connector due to its 37% electrical conductivity. This alloy is in tan - gold colour.

## Value Proposition

- Competitive Pricing
- Flexible LME price fixation
- Product Customization

- Quality Assurance
- Committed to deliveries
- Standard export pallet packing

This data is general technical specification; Binding technical specifications will be as per agreement.

PANBASERESOURCES PVT LTD+91 22 6712 6823sales@panbase.netwww.panbase.net1207, 12th Floor, Mayuresh Chambers, Sector 11, CBD Belapur, Navi Mumbai – 400 614, India